

2510-2513 | 2520-2523**Panelled end platform carts
Double open side platform carts**

Panelled end made of derived timber material boards, surface beech grain.

End panel height: 500 mm



2510 | 2511 | 2512 | 2513 Panelled end platform carts



2520 | 2521 | 2522 | 2523 Double open side platform carts

2530-2533 | 2550-2553**Open sided platform carts
Closed platform carts**

Panelled ends and panelled sides made of derived timber material boards, surface beech grain.

End panel height: 500 mm

Side panel height: 500 mm

Closed platform cart with one detachable side panel.



2530 | 2531 | 2532 | 2533 Open sided platform carts



2550 | 2551 | 2552 | 2553 Closed platform carts

| | Order no. | Capacity kg | Wheel-Ø mm | Outside dimesions L x W x H mm | Platform size L x W mm | Net weight kg | |
|--|-----------|-------------|------------|--------------------------------|------------------------|---------------|--|
| Panelled end platform carts | 2510 | 400 | 160 | 970 x 500 x 950 | 850 x 500 | 26 | |
| | 2511 | 500 | 200 | 1120 x 600 x 990 | 1000 x 600 | 33 | |
| | 2512 | 500 | 200 | 1120 x 700 x 990 | 1000 x 700 | 36 | |
| | 2513 | 500 | 200 | 1320 x 800 x 990 | 1200 x 800 | 42 | |
| Double open-side platform carts | 2520 | 400 | 160 | 1030 x 500 x 950 | 850 x 500 | 30 | |
| | 2521 | 500 | 200 | 1180 x 600 x 990 | 1000 x 600 | 38 | |
| | 2522 | 500 | 200 | 1180 x 700 x 990 | 1000 x 700 | 42 | |
| | 2523 | 500 | 200 | 1380 x 800 x 990 | 1200 x 800 | 48 | |
| Open sided platform carts | 2530 | 400 | 160 | 1030 x 500 x 950 | 850 x 500 | 34 | |
| | 2531 | 500 | 200 | 1180 x 600 x 990 | 1000 x 600 | 42 | |
| | 2532 | 500 | 200 | 1180 x 700 x 990 | 1000 x 700 | 46 | |
| | 2533 | 500 | 200 | 1380 x 800 x 990 | 1200 x 800 | 54 | |
| Closed platform carts | 2550 | 400 | 160 | 1030 x 500 x 950 | 850 x 500 | 38 | |
| | 2551 | 500 | 200 | 1180 x 600 x 990 | 1000 x 600 | 47 | |
| | 2552 | 500 | 200 | 1180 x 700 x 990 | 1000 x 700 | 51 | |
| | 2553 | 500 | 200 | 1380 x 800 x 990 | 1200 x 800 | 59 | |



1510 | 1511 | 1512 | 1513 Panelled end platform carts



1520 | 1521 | 1522 | 1523 Double open-side platform carts



1530 | 1531 | 1532 | 1533 Open sided platform carts



1550 | 1551 | 1552 | 1553 Wire cage carts

1510-1513 | 1520-1523
Panelled end platform carts
Double open side platform carts

Ends made of wire lattice 50 x 50 x 4 mm.
End panel height: 500 mm

1530-1533 | 1550-1553
Open sided platform carts
Wire cage carts

Ends and sides made of wire lattice 50 x 50 x 4 mm.

Height of ends: 500 mm
Height of sides: 500 mm

Wire cage cart with one detachable side.

| | Order no. | Capacity kg | Wheel-Ø mm | Outside dimensions L x W x H mm | Platform size L x W mm | Net weight kg |
|--|-----------|-------------|------------|---------------------------------|------------------------|---------------|
| Panelled end platform carts | 1510 | 400 | 160 | 970 x 500 x 950 | 850 x 500 | 26 |
| | 1511 | 500 | 200 | 1120 x 600 x 990 | 1000 x 600 | 34 |
| | 1512 | 500 | 200 | 1120 x 700 x 990 | 1000 x 700 | 37 |
| | 1513 | 500 | 200 | 1320 x 800 x 990 | 1200 x 800 | 43 |
| Double open-side platform carts | 1520 | 400 | 160 | 1030 x 500 x 950 | 850 x 500 | 30 |
| | 1521 | 500 | 200 | 1180 x 600 x 990 | 1000 x 600 | 38 |
| | 1522 | 500 | 200 | 1180 x 700 x 990 | 1000 x 700 | 42 |
| | 1523 | 500 | 200 | 1380 x 800 x 990 | 1200 x 800 | 48 |
| Open sided platform carts | 1530 | 400 | 160 | 1030 x 500 x 950 | 850 x 500 | 34 |
| | 1531 | 500 | 200 | 1180 x 600 x 990 | 1000 x 600 | 42 |
| | 1532 | 500 | 200 | 1180 x 700 x 990 | 1000 x 700 | 46 |
| | 1533 | 500 | 200 | 1380 x 800 x 990 | 1200 x 800 | 54 |
| Wire cage carts | 1550 | 400 | 160 | 1030 x 500 x 950 | 850 x 500 | 38 |
| | 1551 | 500 | 200 | 1180 x 600 x 990 | 1000 x 600 | 47 |
| | 1552 | 500 | 200 | 1180 x 700 x 990 | 1000 x 700 | 51 |
| | 1553 | 500 | 200 | 1380 x 800 x 990 | 1200 x 800 | 59 |

2560 | 2561 | 2562 | 2563
Box carts

Ends and sides made of derived timber material boards, Height of sides 250 mm. All sides singly detachable.


2560 | 2561 | 2562 | 2563 Box carts

1560 | 1561 | 1562 | 1563 Box carts
1560 | 1561 | 1562 | 1563
Box carts

Ends and sides made of wire lattice 50 x 50 x 4 mm. Height of sides 250 mm, all 4 sides singly detachable.

2541 | 2542 | 2543
Bale trolleys

Ends and sides made of derived timber material boards, surface beech grain. Height of sides 600/750 mm, Interior width = platform width – 60 mm


2541 | 2542 | 2543 Bale trolleys

1541 | 1542 | 1543 Bale trolleys
1541 | 1542 | 1543
Bale trolleys

Ends and sides made of wire lattice 50 x 50 x 4 mm. Height of sides 600/750 mm, Interior width = platform width – 60 mm.

| | Order no. | Capacity kg | Wheel-Ø mm | Outside dimensions L x W x H mm | Platform size L x B mm | Net weight kg | |
|----------------------|-----------|-------------|------------|---------------------------------|------------------------|---------------|--|
| Box carts | 2560 | 400 | 160 | 970 x 500 x 950 | 850 x 500 | 30 | |
| | 2561 | 500 | 200 | 1120 x 600 x 990 | 1000 x 600 | 36 | |
| | 2562 | 500 | 200 | 1120 x 700 x 990 | 1000 x 700 | 40 | |
| | 2563 | 500 | 200 | 1320 x 800 x 990 | 1200 x 800 | 46 | |
| | 1560 | 400 | 160 | 970 x 500 x 950 | 850 x 500 | 29 | |
| | 1561 | 500 | 200 | 1120 x 600 x 990 | 1000 x 600 | 35 | |
| | 1562 | 500 | 200 | 1120 x 700 x 990 | 1000 x 700 | 38 | |
| | 1563 | 500 | 200 | 1320 x 800 x 990 | 1200 x 800 | 44 | |
| Bale trolleys | 2541 | 500 | 200 | 1060 x 600 x 1025 | 1000 x 600 | 42 | |
| | 2542 | 500 | 200 | 1060 x 700 x 1025 | 1000 x 700 | 45 | |
| | 2543 | 500 | 200 | 1260 x 800 x 1025 | 1200 x 800 | 54 | |
| | 1541 | 500 | 200 | 1060 x 600 x 1025 | 1000 x 600 | 40 | |
| | 1542 | 500 | 200 | 1060 x 700 x 1025 | 1000 x 700 | 43 | |
| | 1543 | 500 | 200 | 1260 x 800 x 1025 | 1200 x 800 | 52 | |



8482-1 | 8483-1



8482-3 | 8483-3



8582-1 | 8583-1



8582-3 | 8583-3

Modular system

8482-1 | 8483-1
8582-1 | 8583-1

Parcel carts with end and sides made of wire lattice. Made of tubular and sectional steel, welded and powder-coated blue RAL 5007, bolted construction.

Ends and sides made of wire lattice 100 x 100 x 5 mm. Platform made of special wood material boards, surface beech grain.

Wheels:
2 castor and 2 fixed wheels, solid rubber tyres 160 x 40 or 200 x 50 mm, hubs with roller bearings.

Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Total height/ Useful height
1500 mm / 1230 mm
1800 mm / 1530 mm.

8482-3 | 8483-3
8582-3 | 8583-3

Parcel carts as above, but with double wing doors at the open side panel. Tubular steel frame with wire lattice 100 x 100 x 5 mm. Integrated bolt lock, doors lockable with padlock, wing doors turnable till side panels.

Shelves

Additional charge or price reduction for shelves including 1 pair of support brackets.

| Size mm | Order no. |
|------------|-----------|
| 850 x 500 | E8100ETAW |
| 1000 x 600 | E8101ETAW |
| 1000 x 700 | E8102ETAW |
| 1200 x 800 | E8103ETAW |



Doors closed

Parcel carts with double wing doors

3 closed side panels and 1 open side panel with double wing doors. A very practical and easy to handle solution. The integrated bolt lock which is part of the tubular steel frame is easy to use and absolutely secure. Doors lockable with padlock (not included in delivery).

Doors can be turned till side panels because of special hinges.



Doors turned

| | Capacity kg | Wheel-Ø mm | Platform size LxW mm | Total height mm | Shelf heights mm | Order no. | |
|---|-------------|------------|----------------------|-----------------|------------------|-----------|--|
| Parcel carts with ends and sides made of wire lattice | 500 | 200 | 1000 x 700 | 1500 | 270 | 8482-1 | |
| | 500 | 200 | 1200 x 800 | 1500 | 270 | 8483-1 | |
| | 500 | 200 | 1000 x 700 | 1800 | 270 | 8582-1 | |
| | 500 | 200 | 1200 x 800 | 1800 | 270 | 8583-1 | |
| Parcel carts with ends and sides made of wire lattice and double wing doors | 500 | 200 | 1000 x 700 | 1500 | 270 | 8482-3 | |
| | 500 | 200 | 1200 x 800 | 1500 | 270 | 8483-3 | |
| | 500 | 200 | 1000 x 700 | 1800 | 270 | 8582-3 | |
| | 500 | 200 | 1200 x 800 | 1800 | 270 | 8583-3 | |

BOX CARTS

For safe transport and storage • Robust sectional/tubular steel construction • Powder coated blue RAL 5007 • Optionally open or with 2-leaf door • 2 interlocking systems: functional pad-lock lockable rod system (easy to handle, replaceable locks) or elegant vertical locking rod (with turning lever and cylinder lock) • Detachable wood material shelves, surface beech grain, edges with PVC-paste application • Shelf supports mountable as required in intervals of 100 mm • Sides, roof and doors optionally in close-mesh wire lattice made of galvanized steel or aluminium sheet • 2 castor wheels and 2 fixed wheels, elastic solid rubber tyres, hubs with roller bearings • Castors with wheel lock • High capacity • Low rolling resistance and high resilience • Special edition with high-quality roller shutter made of aluminium



Box carts

Tubular steel and profile steel welded, powder coated blue RAL 5007. Platform made of derived timber material board, surface beech grain.

2 castor and 2 fixed wheels, solid rubber tyres, hubs with roller bearings. Castors with wheel locks, **according to the European Standard EN 1757-3 (safety of platform trolleys).**

2772 | 2773

Wire cage cart with tubular steel superstructure, wire lattice 50 x 50 x 4 mm, welded. Bolted modular version, powder-coated.

Useful height: 700 mm.



2772 | 2773 Wire cage carts



2762 | 2763 Wire cage carts with cover

2762 | 2763

Wire cage cart with angular steel superstructure, wire lattice 50 x 50 x 4mm, welded. Cover double collapsible. Ring-eyelets for padlocks.

Useful height: 800 mm.



2872 | 2873 Wooden box carts



2852 | 2853 Wooden box carts with cover

2872 | 2873

Wooden box cart, as 2772/3, but all sides of derived timber material boards, surface beech grain.

2852 | 2853

Wooden box cart with angular steel superstructure, platform, sides and cover made of derived timber material boards, surface beech grain. Cover double collapsible, ring eyelets for padlocks.

Useful height: 800 mm.

| | Order no. | Capacity kg | Wheel Ø mm | Outside dimensions L x W x H mm | Platform size L x W mm | Net weight kg | |
|------------------------------------|-----------|-------------|------------|---------------------------------|------------------------|---------------|--|
| Wire cage carts | 2772 | 500 | 200 | 1060 x 715 x 1075 | 1000 x 700 | 54 | |
| | 2773 | 500 | 200 | 1260 x 815 x 1075 | 1200 x 800 | 62 | |
| Wooden box carts | 2872 | 500 | 200 | 1060 x 715 x 1075 | 1000 x 700 | 66 | |
| | 2873 | 500 | 200 | 1260 x 815 x 1075 | 1200 x 800 | 72 | |
| Wire cage carts with cover | 2762 | 500 | 200 | 1130 x 725 x 1120 | 1000 x 700 | 70 | |
| | 2763 | 500 | 200 | 1330 x 825 x 1120 | 1200 x 800 | 84 | |
| Wooden box carts with cover | 2852 | 500 | 200 | 1130 x 725 x 1120 | 1000 x 700 | 87 | |
| | 2853 | 500 | 200 | 1330 x 825 x 1120 | 1200 x 800 | 100 | |



2842 | 2843 Sheet steel box carts



2862 | 2863 Sheet steel box carts with cover

Sheet steel box carts

Tubular steel and profile steel welded, powder coated blue RAL 5007. Platforms made of sheet steel, powder coated or galvanized.

2 castor and 2 fixed wheels, solid rubber tyres, hubs with roller bearings. Castors with wheel locks, **according to the European Standard EN 1757-3 (safety of platform trolleys).**

2842 | 2843

Sheet steel box cart, angle steel construction, sides made of sheet steel, welded and powder coated.

Useful height: 800 mm.

2862 | 2863

Construction as 2842/2843, but with one-piece cover, to be opened by means of gas pressure spring, ring eyelets for padlocks.

2822 | 2823

Construction as 2842/2843, but with sides of galvanized steel plates, glued in place.

Useful height: 800 mm.

2832 | 2833

Construction as 2822/2833, but with one-piece cover as with 2862/2863.



2822 | 2823 Sheet steel box carts



2832 | 2833 Sheet steel box carts with cover

| | Order no. | Capacity kg | Wheel Ø mm | Outside dimensions L x W x H mm | Platform size L x W mm | Net weight kg | |
|----------------------------------|-----------|-------------|------------|---------------------------------|------------------------|---------------|--|
| Sheet steel box carts | 2842 | 500 | 200 | 1130 x 725 x 1070 | 1000 x 700 | 83 | |
| | 2843 | 500 | 200 | 1330 x 825 x 1070 | 1200 x 800 | 98 | |
| Sheet steel box carts with cover | 2862 | 500 | 200 | 1150 x 730 x 1090 | 1000 x 700 | 93 | |
| | 2863 | 500 | 200 | 1350 x 830 x 1090 | 1200 x 800 | 110 | |
| Sheet steel box carts | 2822 | 500 | 200 | 1130 x 725 x 1070 | 1000 x 700 | 68 | |
| | 2823 | 500 | 200 | 1330 x 825 x 1070 | 1200 x 800 | 83 | |
| Sheet steel box carts with cover | 2832 | 500 | 200 | 1150 x 730 x 1090 | 1000 x 700 | 79 | |
| | 2833 | 500 | 200 | 1350 x 830 x 1090 | 1200 x 800 | 90 | |

3392 | 3393**Box carts**

Shelved trolley in angle steel construction with tubular handlebar. Ends, 1 side and top fitted with wire lattice 40 x 40 x 4 mm, completely welded and powder-coated. 1 fixed and 4 detachable wood material shelves, surface beech grain.

2 castor wheels and 2 fixed wheels, **solid rubber tyres, hubs with roller bearings.**

Castors with wheel locks, **according to the European Standard EN 1757-3 (safety of platform trolleys).**

Shelf heights:

285/575/875/1175/1475 mm.

Clearance between shelves 280 mm.

Outside dimensions L x W x H:

3392 = 1170 x 700 x 1790 mm.

3393 = 1370 x 800 x 1790 mm.

Capacity per shelf 90 kg

**3392 | 3393****4392 | 4393** Padlock lockable rod system**5392 | 5393 | 4392 | 4393**

With 2-leaf door of angle steel with welded wire lattice on open side.

Shelf heights:

285/575/875/1175/1475 mm.

Clearance between shelves 280 mm.

Outside dimensions L x W x H:

5392 = 1170 x 800 x 1790 mm.

5393 = 1370 x 900 x 1790 mm.

Outside dimensions L x W x H:

4392 = 1170 x 740 x 1790 mm.

4393 = 1370 x 840 x 1790 mm.

**5392 | 5393** Vertical locking rod**Vertical locking rod**

With turning lever and cylinder lock.

**Padlock lockable rod system**

Easy to handle, replaceable locks. Locking rod does not project.

Delivery without padlocks.

**Shelf support**

Variable use of support rods, distance 100 mm.

Accessories on page 92

| | Order no. | Capacity kg | Wheel Ø mm | Platform size L x W mm | No. of shelves | Net weight kg | Add. shelves | |
|------------------|-----------|-------------|------------|------------------------|----------------|---------------|--------------|--|
| | | | | | | | Order no. | |
| Box carts | 3392 | 750 | 200 | 1000 x 680 | 5 | 133 | 1325 | |
| | 3393 | 750 | 200 | 1200 x 780 | 5 | 151 | 1926 | |
| | 4392 | 750 | 200 | 1000 x 680 | 5 | 145 | 1325 | |
| | 4393 | 750 | 200 | 1200 x 780 | 5 | 176 | 1926 | |
| | 5392 | 750 | 200 | 1000 x 680 | 5 | 147 | 1325 | |
| | 5393 | 750 | 200 | 1200 x 780 | 5 | 178 | 1926 | |

BOX CARTS 750 KG



5492 | 5493 Galvanized steel sheet



5592 | 5593 Aluminium sheet



5692 | 5693



5692 | 5693 Closed



5692 | 5693 Open

5492/5493

Box cart in angle steel construction with tubular handlebar, powder coated. Ends, 1 side, folding door and roof covered with galvanized 1 mm steel sheet.

Double wing door made of angle steel with vertical locking rod and integrated cylinder lock. 1 fixed and 4 detachable wood material shelves, surface beech grain.

2 castor wheels and 2 fixed wheels, elastic solid rubber tyres, hubs with roller bearings. Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Shelf heights 285/575/875/1175/1475 mm. Clearance between shelves 280 mm.

Outside dimensions L x W x H:
5492 = 1170 x 700 x 1790 mm.
5493 = 1370 x 800 x 1790 mm.

5592 | 5593

as 5492/5493, but ends, side, folding door and roof covered with 1,5 mm aluminium sheet. Capacity per shelf 90 kg

5692 | 5693

Box cart in angle steel construction with tubular handlebar. Ends, 1 side, folding door and roof covered with 1,5 mm aluminium sheet.

1 side panel with easy-running roller shutter made of aluminium hollow section, with recessed grip and cylinder lock. 1 fixed and 4 detachable shelves, made of coated Multiplex board.

2 castor wheels and 2 fixed wheels, elastic solid rubber tyres, hubs with roller bearings. Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Protective strip all around base frame made of plastic profiles.

Shelf heights 285/575/875/1175/1475 mm. Clearance between shelves 280 mm.

Outside dimensions L x W x H:
5692 = 1170 x 700 x 1790 mm.
5693 = 1370 x 800 x 1790 mm.

| | Order no. | Capacity kg | Wheel Ø mm | Platform size L x W mm | No. of shelves | Net weight kg | Add. shelves | |
|------------------|-----------|-------------|------------|------------------------|----------------|---------------|--------------|--|
| | | | | | | | Order no. | |
| Box carts | 5492 | 750 | 200 | 1000 x 680 | 5 | 162 | 1325 | |
| | 5493 | 750 | 200 | 1200 x 780 | 5 | 199 | 1926 | |
| | 5592 | 750 | 200 | 1000 x 680 | 5 | 141 | 1325 | |
| | 5593 | 750 | 200 | 1200 x 780 | 5 | 173 | 1926 | |
| | 5692 | 750 | 200 | 1000 x 680 | 5 | 140 | 1927 | |
| | 5693 | 750 | 200 | 1200 x 780 | 5 | 172 | 1928 | |

Accessories on page 92

SHEET METAL DUMP TRUCKS | SELF-TILTING BOXES

Volume 250 – 1200 litres • Load capacity 500 – 2500 kg • Robust sheet steel dump truck neatly welded • Chassis welded from sheet steel mouldings • With integrated stacker pockets • Powder coated blue RAL 5007 • Dump truck with 2 castors and 2 fixed wheels • Castors with wheel locks • Self-tilting truck without wheels, optionally with wheels • Dump trucks are appropriate for medium loads • The tipping process is initiated by lifting-up • Self-tilting trucks are appropriate for high loads • The tilting process starts automatically after releasing the lock • Can be activated via traction cable from fork lift truck driver's seat



4701-4703

Sheet metal dump trucks made of 2 mm thick steel sheet, with double-folded top rim. Welded oil-tight.

Chassis made of 3 mm thick canted steel sheet, with integrated stacker pockets. Kickplate and tilt lock, tubular steel handle. Powder coated blue RAL 5007.

Fitted with 2 castor wheels and 2 fixed wheels, solid rubber tyres 200 x 50 mm, hubs with roller bearings.

Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Suitable for pushing and for stacking.



4701



4704

Fitted with 2 castor wheels and 2 fixed wheels, elasticated solid rubber tyres 200 x 50 mm, hubs with ball bearings. Castors with wheel locks.

Suitable for pushing and for stacking.



4702-4704

Drainage tap

with filter to separate liquids from solids. Add 'A' suffix to the order number of the relevant truck (e.g. 4701A).



Drainage tap



Example of use:
Sheet metal dump truck as bin for wood chips



Sheet metal dump truck as waste bin with forklift truck.

| Dimensions of forklift sleeves | Order no. | Contents litres | A mm | B mm | C mm | D mm |
|--------------------------------|-----------|-----------------|------|------|------|------|
| | 4701 | 250 | 194 | 203 | 603 | 70 |
| | 4702 | 450 | 194 | 203 | 603 | 70 |
| | 4703 | 600 | 194 | 327 | 727 | 70 |
| | 4704 | 800 | 194 | 578 | 978 | 70 |

| | Order no. | Contents litres | Capacity kg | Box size L x W x H mm | Outside dimensions L x W x H mm | Dumping edge height in mm |
|-------------------------|-----------|-----------------|-------------|-----------------------|---------------------------------|---------------------------|
| Sheet metal dump trucks | 4701 | 250 | 500 | 1202 x 655 x 390 | 1332 x 713 x 766 | 766 |
| | 4702 | 450 | 500 | 1212 x 675 x 695 | 1353 x 732 x 1065 | 721 |
| | 4703 | 600 | 500 | 1320 x 800 x 715 | 1465 x 858 x 1088 | 828 |
| | 4704 | 800 | 800 | 1320 x 970 x 715 | 1465 x 1108 x 1088 | 828 |



6030 | 6060 | 6090 | 6120

Example of use:



Self-tilting box with set of wheels.



Self-tilting box as waste bin with fork-lift.

Self-tilting boxes 6030 | 6060 | 6090 | 6120

Self-tilting, fully-emptying boxes for tipping bulk goods automatically.

Self-tilting boxes need not to be lifted for emptying. The empty box moves automatically back into loading position.

Sturdy welded 3 mm sheetsteel design, powder coated in RAL 5007 blue.

Standard-fitted fork-lift sleeves, anti-roll safety device and tilt lock. Link chain as anti-skidding and safety device. Traction cable to activate tilting mechanism, operated from fork-lift truck driver's seat.



6230 | 6250 | 6275

Example of use:



Tipping container with set of wheels.



Tipping container as a waste container with fork-lift.

Tipping container 6230 | 6250 | 6275

for tipping bulk goods - even extremely light goods automatically.

Particularly low construction.

Tipping containers must be lifted with a fork lift for emptying. By dropping the box to the ground the container will be adjusted automatically and moved back into loading position. Sturdy welded 2 mm sheetsteel design, powder coated in RAL 5007 blue. Standard-fitted fork-lift sleeves, anti-roll safety device and tilt lock. Link chain as anti-skidding and safety device. Traction cable to activate tilting mechanism, operated from fork-lift truck driver's seat.

| Dimensions of forklift sleeves | Order no. | Contents litres | A mm | B mm | C mm | D mm |
|--------------------------------|-----------|-----------------|------|------|------|------|
| | 6030 | 350 | 194 | 192 | 592 | 80 |
| | 6060 | 600 | 194 | 582 | 982 | 80 |
| | 6090 | 900 | 194 | 582 | 982 | 80 |
| | 6120 | 1200 | 194 | 582 | 982 | 80 |
| | 6230 | 300 | 200 | 80 | 492 | 60 |
| | 6250 | 500 | 200 | 280 | 692 | 60 |
| | 6275 | 750 | 200 | 490 | 902 | 60 |

| | Order no. | Capacity kg | Contents litres | Length mm | Width mm | Height mm | Dumping edge height mm without rollers | Dumping edge height mm with rollers | Net weight kg |
|---------------------------|-----------|-------------|-----------------|-----------|----------|-----------|--|-------------------------------------|---------------|
| Self-tilting boxes | 6030 | 1000 | 350 | 1300 | 730 | 830 | 720 | 955 | 112 |
| | 6060 | 1500 | 600 | 1300 | 1120 | 830 | 720 | 955 | 132 |
| | 6090 | 2000 | 900 | 1300 | 1620 | 830 | 720 | 955 | 162 |
| | 6120 | 2500 | 1200 | 1758 | 1182 | 1125 | 1015 | 1250 | 195 |
| Tipping container | 6230 | 750 | 300 | 1315 | 690 | 580 | 405 | 640 | 68 |
| | 6250 | 1000 | 500 | 1390 | 890 | 680 | 505 | 740 | 86 |
| | 6275 | 1000 | 750 | 1390 | 1300 | 680 | 505 | 740 | 108 |

Set of wheels

2 castor wheels and 2 fixed-wheels made of polyamide, size 200 x 50 mm, fitted underneath the fork-lift sleeves (height +240 mm). Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

| Capacity | Order no. |
|------------------------------|-----------|
| for 6030/6060/6230/6250/6275 | |
| 1500 kg | 1567 |
| for 6090/6120 | |
| 2500 kg | 1568 |

Drainage tap

with filter to separate liquids from solids. Add 'A' suffix to the order number of the relevant truck (e.g. 6030A).



6971 Lifting rolls



6977 Angle rolls



6971 Lifting rolls

for the transport of heavy cupboards etc., steel plate frame galvanized yellow. Contact area with rubber cover, wheel with polyurethane tyres.

Claw height:
lowered = 12 mm,
lifted max. = 50 mm.

Scope of delivery:
2 lifting rolls and 1 lever rod.

Handling:
Lift load with lever rod, place claw of the lifting roll underneath the load and finally lift load completely by shifting the control lever by means of the lever rod. Proceed exactly in the same way on the opposite side with the second lifting roll and the load can be moved.

Angle rolls

for moving of furniture or similar box-shaped objects. Low loading edge and safe transport.

Steel plate housing welded, coated signal red, loading platform with non-slip covering. 3 solid rubber castors 50 x 20 mm.

Width 366 mm
Depth 204 mm
Height 85 mm
Loading height 15 mm

Scope of delivery: 1 set = 4 pieces (in a plastic box)



6608 | 6610 | 6612 Pallet top frames



6708 | 6710 | 6712 Pallet stacker frames



6608 | 6610 | 6612 Pallet top frames

Steel tube construction with welded wire lattice 100 x 50 x 4, galvanized.

Half of one longitudinal side folding down. Suitable for Euro pallets. Flat packed for easy self assembly. Collapsible for storage and transport, low space requirement. Stackable in 4 layers.

6708 | 6710 | 6712 Pallet stacker frames

Steel tube construction with clamping joints and stacker corners.

Sturdy construction, hot galvanized, stackable in 4 layers. Delivery in pairs.

| | Order no. | Capacity per pc. kg | Capacity per pair kg | Wheel size Ø x W mm | Net weight 4 pcs. kg | Net weight per pair kg |
|---------------|-----------|---------------------|----------------------|---------------------|----------------------|------------------------|
| Lifting rolls | 6971 | - | 1000 | 138 x 28 | - | 10 |
| Angle rolls | 6977 | 150 | - | 50 x 20 | 8 | - |

| | Order no. | L x W mm | Stock height mm | Useful height mm | Capacity kg | Net weight kg |
|-----------------------|-----------|------------|-----------------|------------------|-------------|---------------|
| Pallet top frames | 6608 | 1200 x 800 | 800 | 800 | 1500 | 30 |
| | 6610 | 1200 x 800 | 1000 | 1000 | 1500 | 34,5 |
| | 6612 | 1200 x 800 | 1200 | 1200 | 1500 | 39 |
| Pallet stacker frames | 6708 | 1200 x 800 | 800 | 770 | 1500 | 20 |
| | 6710 | 1200 x 800 | 1000 | 970 | 1500 | 21,5 |
| | 6712 | 1200 x 800 | 1200 | 1170 | 1500 | 23 |