



- First class monolithic polyamide 6 wheel, neutral color, corrosion resistant.

- Roller bearing


- Temperature range from -20°C to 80°C


- Maximum working speed 4 km/h

- Extra heavy duty housings EP80J

															Codes
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Load cap. (kg)	(Weight) kg	

	NPP-J06 J07															
	100	35	138	100x85	80x60	11	40	-	-	-	-	-	-	350	1.12	J07 210 100035
	125	35	169.5	140x110	105x80/75	11	47	-	-	-	-	-	400	1.97	J07 210 125035	
	150	45	193	140x110	105x80/75	11	47	-	-	-	-	-	500	2.17	J07 210 150045	
	200	50	250	140x110	105x80/75	11	65	-	-	-	-	-	950	3.85	J07 210 200050	

	NPPFR-J06 J07															
	100	35	138	100x85	80x60	11	40	-	-	-	-	-	105	350	1.42	J06 214 100035
	125	45	169.5	140x110	105x80/75	11	47	-	-	-	-	-	112	400	2.37	J07 214 125045
	150	45	193	140x110	105x80/75	11	47	-	-	-	-	-	112	500	2.57	J07 214 150045
	200	50	250	140x110	105x80/75	11	65	-	-	-	-	-	125	950	4.35	J07 214 200050

	NFP-J06 J07															
	100	35	138	100x85	80x60	11	-	-	-	-	-	-	-	350	0,58	J06 220 100035
	125	45	169.5	140x110	105x80/75	11	-	-	-	-	-	-	-	400	1.11	J07 220 125045
	150	45	193	140x110	105x80/75	11	-	-	-	-	-	-	-	500	1,33	J07 220 150045
	200	50	250	140x110	105x80/75	11	-	-	-	-	-	-	950	2.03	J07 220 200050	