
























- Injected PU tread, hardness 95±3 Sh.A.
- First class PA 6 wheel centre, neutral color, corrosion resistant.
- Plain or roller bearing
- T° range from -20°C to 70°C
- Maximum working speed 4 kmh
- Standard housing M80A


																		Codes
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Load cap. (kg)	(Weight) kg	


 <b>PP-A08</b>	50	18	69	41x41	30x30	5.5	23	-	-	-	-	-	-	-	-	35	0.19	A08 210 050018	
	60	24	87	60x60	46x46	6.5	23	-	-	-	-	-	-	-	-	-	50	0.40	A08 210 060024
	80	30	107	100x83	80x60	9	37	-	-	-	-	-	-	-	-	-	120	0.52	A08 210 080030
	100	35	128	100x83	80x60	9	37	-	-	-	-	-	-	-	-	-	170	0.62	A08 210 100035
	125L	35	155	100x83	80x60	9	37	-	-	-	-	-	-	-	-	-	210	0.80	D08 210 125035
	125	35	155	100x85	80x60	9	45	-	-	-	-	-	-	-	-	-	220	1.05	A08 210 125035
	150	40	182	100x85	80x60	9	45	-	-	-	-	-	-	-	-	-	220	1.25	A08 210 150040
175	45	219	140x110	105x80/75	11	55	-	-	-	-	-	-	-	-	-	300	2.24	A08 210 175045	
200	50	240	140x110	105x80/75	11	55	-	-	-	-	-	-	-	-	-	300	2.45	A08 210 200050	


 <b>PPFA-A08</b>	80	30	127	100x83	80x60	9	37	-	-	-	-	-	-	112	-	120	0.82	A08 212 080030	
	100	30	128	100x83	80x60	9	37	-	-	-	-	-	-	-	112	-	170	0.92	A08 212 100035
	125L	35	155	100x83	80x60	9	37	-	-	-	-	-	-	112	-	210	1.25	D08 212 125035	
	125	35	155	100x85	80x60	9	45	-	-	-	-	-	-	-	132	-	220	1.45	A08 212 125035
	150	40	182	100x85	80x60	9	45	-	-	-	-	-	-	-	132	-	220	1.65	A08 212 150040
	175	45	219	140x110	105x80/75	11	55	-	-	-	-	-	-	-	148	-	300	2.75	A08 212 175045
	200	50	240	140x110	105x80/75	11	55	-	-	-	-	-	-	-	148	-	300	2.95	A08 212 200050


 <b>PF-A08</b>	50	18	69	49x45	30x30	5.5	-	-	-	-	-	-	-	-	-	35	0.11	A08 220 050018	
	60	22	87	60x60	46x46	6.5	-	-	-	-	-	-	-	-	-	-	50	0.18	A08 220 060024
	80	30	107.5	100x83	80x60	9	-	-	-	-	-	-	-	-	-	-	180	0.35	A08 220 080030
	100	35	128	100x83	80x60	9	-	-	-	-	-	-	-	-	-	-	200	0.40	A08 220 100035
	125L	40	155	100x83	80x60	9	-	-	-	-	-	-	-	-	-	-	210	0.52	D08 220 125035
	125	40	155.5	100x85	80x60	9	-	-	-	-	-	-	-	-	-	-	220	0.65	A08 220 125035
	150	40	182.5	100x85	80x60	9	-	-	-	-	-	-	-	-	-	-	230	0.85	A08 220 150040
175	45	219.5	140x110	105x80/75	11	-	-	-	-	-	-	-	-	-	-	300	1.40	A08 220 175045	
200	50	240	140x110	105x80/75	11	-	-	-	-	-	-	-	-	-	-	300	1.68	A08 220 200050	


 <b>PPFP-A08</b>	50	18	66	-	-	-	23	Ø35	Ø8	-	-	-	-	-	-	35	0.13	A08 230 050018	
	60	24	87	-	-	-	23	Ø47.5	Ø10	-	-	-	-	-	-	-	50	0.25	A08 230 060024
	80	30	104	-	-	-	37	Ø68	Ø14	-	-	-	-	-	-	-	120	0.44	A08 230 080030
	100	35	128	-	-	-	37	Ø68	Ø14	-	-	-	-	-	-	-	170	0.54	A08 230 100035
	125L	35	152	-	-	-	37	Ø68	Ø14	-	-	-	-	-	-	-	210	0.73	D08 230 125035
	125	35	152	-	-	-	45	Ø82	Ø16	-	-	-	-	-	-	-	220	0.61	A08 230 125035
	150	40	179	-	-	-	45	Ø82	Ø16	-	-	-	-	-	-	-	220	0.78	A08 230 150040
175	45	216	-	-	-	55	Ø100.5	Ø18	-	-	-	-	-	-	-	300	1.48	A08 230 175045	
200	50	237	-	-	-	55	Ø100.5	Ø18	-	-	-	-	-	-	-	300	1.61	A08 230 200050	

 <b>PPPPFA-A08</b>	50	18	66	-	-	-	23	Ø35	Ø8	-	-	-	80	-	-	35	0.16	A08 232 050018
	60	24	87	-	-	-	23	Ø47.5	Ø10	-	-	-	80	-	-	50	0.30	A08 232 060024
	80	30	104	-	-	-	37	Ø68	Ø14	-	-	-	112	-	-	120	0.54	A08 232 080030
	100	35	128	-	-	-	37	Ø68	Ø14	-	-	-	112	-	-	170	0.64	A08 232 100035
	125L	35	152	-	-	-	37	Ø68	Ø14	-	-	-	112	-	-	210	0.83	D08 232 125035
	125	35	152	-	-	-	45	Ø82	Ø16	-	-	-	132	-	-	220	0.71	A08 232 125035
	150	40	179	-	-	-	45	Ø82	Ø16	-	-	-	132	-	-	220	0.88	A08 232 150040
175	45	216	-	-	-	55	Ø100.5	Ø18	-	-	-	148	-	-	300	1.88	A08 232 175045	
200	50	237	-	-	-	55	Ø100.5	Ø18	-	-	-	148	-	-	300	2.01	A08 232 200050	

 <b>PPC-A08</b>	80	30	104	-	-	-	37	Ø14	-	Ø20	50	-	-	-	-	120	0.66	A08 240 080030	
	100	35	128	-	-	-	37	Ø68	-	Ø20	50	-	-	-	-	-	170	0.72	A08 240 100035
	125L	35	152	-	-	-	37	Ø68	-	Ø22	50	-	-	-	-	-	210	0.93	D08 250 125035
	125	35	152	-	-	-	45	Ø82	-	Ø22	50	-	-	-	-	-	220	1.05	A08 250 125035
	150	40	179	-	-	-	45	Ø82	-	Ø22	50	-	-	-	-	-	220	1.30	A08 250 150040
	175	45	216	-	-	-	55	Ø100.5	-	Ø27	60	-	-	-	-	-	300	1.95	A08 260 175045
	200	50	237	-	-	-	55	Ø100.5	-	Ø27	60	-	-	-	-	-	300	2.38	A08 260 200050

 <b>PPCFA-A08</b>	80	30	104	-	-	-	37	Ø14	-	Ø20	50	112	-	-	-	120	0.76	A08 242 080030	
	100	35	128	-	-	-	37	Ø68	-	Ø20	50	112	-	-	-	-	170	0.82	A08 242 100035
	125L	35	152	-	-	-	37	Ø68	-	Ø22	50	112	-	-	-	-	210	1.03	D08 252 125035
	125	35	152	-	-	-	45	Ø82	-	Ø22	50	132	-	-	-	-	220	1.15	A08 252 125035
	150	40	179	-	-	-	45	Ø82	-	Ø22	50	132	-	-	-	-	220	1.50	A08 252 150035
	175	45	216	-	-	-	55	Ø100.5	-	Ø27	60	148	-	-	-	-	300	2.35	A08 262 175045
	200	50	237	-	-	-	55	Ø100.5	-	Ø27	60	148	-	-	-	-	300	2.78	A08 262 200050

 <b>PPV-A08</b>	50	18	66	-	-	-	23	23	-	M10	20	-	-	-	-	35	0.15	A08 280 050018	
	60	24	87	-	-	-	23	Ø47.5	-	M10	20	-	-	-	-	-	50	0.27	A08 280 060024
	80	30	104	-	-	-	37	Ø68	-	M10	30	-	-	-	-	-	120	0.64	A08 280 080030
	100	35	128	-	-	-	37	Ø68	-	M10	30	-	-	-	-	-	170	0.50	A08 280 100035
	125L	35	152	-	-	-	37	Ø68	-	M12	30	-	-	-	-	-	210	0.78	D08 290 125035
	125	35	152	-	-	-	45	Ø82	-	Ø22	50	-	-	-	-	-	220	0.87	A08 290 125035
	150	40	179	-	-	-	45	Ø82	-	M12	30	-	-	-	-	-	220	1.12	A08 290 150040

 <b>PPVFA-A08</b>	50	18	66	-	-	-	23	23	-	M10	20	80	-	-	-	35	0.20	A08 282 050018	
	60	22	87	-	-	-	23	Ø47.5	-	M10	20	80	-	-	-	-	50	0.32	A08 282 060024
	80	30	104	-	-	-	37	Ø68	-	M10	30	112	-	-	-	-	120	0.64	A08 282 080030
	100	35	128	-	-	-	37	Ø68	-	M10	30	112	-	-	-	-	170	0.70	A08 282 100035
	125L	35	152	-	-	-	37	Ø68	-	M12	30	112	-	-	-	-	210	0.88	D08 292 125035
	125	35	152	-	-	-	45	Ø82	-	Ø22	50	132	-	-	-	-	220	1.07	A08 292 125035
	150	40	179	-	-	-	45	Ø82	-	M12	30	132	-	-	-	-	220	1.32	A08 292 150040