



- Elastik injected PU tread, hardness 82±2 Sh.A.
- First class PA 6 wheel centre, neutral color, corrosion resistant.
- Roller bearing
- T° range from -20°C to 70°C
- Maximum working speed 4 kmh
- Heavy duty housing P80G

| | | | | | | | | | | | | | | | | Codes |
|-----------------------|------------|-----------|-----|---------|-----------|----|----|----|----|----|----|----|-----|----------------|-------------|----------------|
| | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | Load cap. (kg) | (Weight) kg | |
| PPMP-G49 | 100 | 33 | 133 | 100x83 | 80x60 | 9 | 37 | - | - | - | - | - | - | 200 | 1,04 | G49 210 100033 |
| | 125 | 35 | 161 | 100x83 | 80x60 | 9 | 45 | - | - | - | - | - | - | 350 | 1,49 | G49 210 125035 |
| | 125 | 40 | 161 | 100x85 | 80x60 | 9 | 45 | - | - | - | - | - | - | 350 | 1,58 | G49 210 125040 |
| | 150 | 40 | 182 | 100x85 | 80x60 | 9 | 45 | - | - | - | - | - | - | 300 | 1,92 | G49 210 150040 |
| | 175 | 45 | 219 | 140x110 | 105x80/75 | 11 | 55 | - | - | - | - | - | - | 480 | 2,55 | G49 210 175045 |
| | 200 | 50 | 240 | 140x110 | 105x80/75 | 11 | 55 | - | - | - | - | - | - | 600 | 2,80 | G49 210 200050 |
| PPMPFR-G49 | 100 | 33 | 133 | 100x83 | 80x60 | 9 | 37 | - | - | - | - | - | 105 | 200 | 1,34 | G49 214 100033 |
| | 125 | 35 | 161 | 100x83 | 80x60 | 9 | 45 | - | - | - | - | - | 108 | 350 | 1,79 | G49 214 125035 |
| | 125 | 40 | 161 | 100x85 | 80x60 | 9 | 45 | - | - | - | - | - | 108 | 350 | 1,88 | G49 214 125040 |
| | 150 | 40 | 182 | 100x85 | 80x60 | 9 | 45 | - | - | - | - | - | 108 | 300 | 2,33 | G49 214 150040 |
| | 175 | 45 | 219 | 140x110 | 105x80/75 | 11 | 55 | - | - | - | - | - | 125 | 480 | 3,06 | G49 214 175045 |
| | 200 | 50 | 240 | 140x110 | 105x80/75 | 11 | 55 | - | - | - | - | - | 125 | 600 | 3,30 | G49 214 200050 |
| PFMP-G49 | 100 | 33 | 133 | 100x83 | 80x60 | 9 | - | - | - | - | - | - | - | 200 | 0,73 | G49 220 100033 |
| | 125 | 35 | 161 | 100x83 | 80x60 | 9 | - | - | - | - | - | - | - | 350 | 1,20 | G49 220 125035 |
| | 125 | 40 | 161 | 100x85 | 80x60 | 9 | - | - | - | - | - | - | - | 350 | 1,37 | G49 220 125040 |
| | 150 | 40 | 193 | 100x85 | 80x60 | 9 | - | - | - | - | - | - | - | 300 | 1,64 | G49 220 150040 |
| | 175 | 45 | 229 | 140x110 | 105x80/75 | 11 | - | - | - | - | - | - | - | 480 | 2,55 | G49 220 175045 |
| | 200 | 50 | 240 | 140x110 | 105x80/75 | 11 | - | - | - | - | - | - | - | 600 | 2,16 | G49 220 200050 |