





















- Injected PU tread, hardness 95±3 Sh.A
- First class PA 6 wheel centre, neutral color, corrosion resistant.
- Roller bearings
- Temperature range from -20°C to 70°C
- Maximum working speed 4 kmh
- Extra heavy duty housing P80G

																Codes
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Load cap. (kg)	(Weight) kg	
 PPPJ08	100	35	138	100x85	80x60	11	40	-	-	-	-	-	-	200	1.18	J08 210 100035
	125	35	169.5	140x110	105x80/75	11	47	-	-	-	-	-	-	300	2.12	J08 210 125035
	150	40	193	140x110	105x80/75	11	47	-	-	-	-	-	-	350	2.32	J08 210 150040
	200	50	250	140x110	105x80/75	11	65	-	-	-	-	-	-	500	4.23	J08 210 200050
 PPPFR08	100	35	138	100x85	80x60	11	40	-	-	-	-	-	105	200	1.48	J08 214 100035
	125	35	169.5	140x110	105x80/75	11	47	-	-	-	-	-	112	300	2.52	J08 214 125035
	150	40	193	140x110	105x80/75	11	47	-	-	-	-	-	112	350	2.72	J08 214 150040
	200	50	250	140x110	105x80/75	11	65	-	-	-	-	-	125	500	4.73	J08 214 200050
 PFPJ08	100	35	138	100x85	80x60	11	-	-	-	-	-	-	-	200	0.64	J08 220 100035
	125	35	169.5	140x110	105x80/75	11	-	-	-	-	-	-	-	300	1.26	J08 220 125035
	150	40	193	140x110	105x80/75	11	-	-	-	-	-	-	-	350	1.48	J08 220 150040
	200	50	250	140x110	105x80/75	11	-	-	-	-	-	-	-	500	2.41	J08 220 200050