






- Elastik injected PU tread, hardness 97±3 Sh.A.
- First class PA 6 wheel centre, neutral color, corrosion resistant.
- Roller bearing
- T° range from -20°C to 70°C
- Maximum working speed 4 kmh
- Extra heavy duty housing EP80J

																	Codes
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Load cap. (kg)	(Weight) kg	

	PPP-J49	100	33	138	100x85	80x60	11	40	-	-	-	-	-	-	200	1.28	J49 210 100033
		125	35	169.5	140x110	105x80/75	11	47	-	-	-	-	-	-	350	2.37	J49 210 125035
		125	40	169.5	140x110	105x80/75	11	47	-	-	-	-	-	-	350	2.56	J49 210 125040
		150	40	193	140x110	105x80/75	11	47	-	-	-	-	-	-	300	4.45	J49 210 150040
		175	45	223.5	140x110	105x80/75	12	65	-	-	-	-	-	-	480	4.20	J49 210 175045
	200	50	250	140x110	105x80/75	11	65	-	-	-	-	-	-	600	5.12	J49 210 200050	

	PPFR-J49	100	33	138	100x85	80x60	11	40	-	-	-	-	-	105	200	1.58	J49 214 100033
		125	35	169.5	140x110	105x80/75	11	47	-	-	-	-	-	112	350	2.87	J49 214 125035
		125	40	169.5	140x110	105x80/75	11	47	-	-	-	-	-	112	350	3.06	J49 214 125040
		150	40	193	140x110	105x80/75	11	47	-	-	-	-	-	125	300	4.85	J49 214 150040
		175	45	223.5	140x110	105x80/75	12	65	-	-	-	-	-	125	480	4.70	J49 214 175045
		200	50	250	140x110	105x80/75	11	65	-	-	-	-	-	138	600	5.62	J49 214 200050

	PFP-J49	100	33	138	100x85	80x60	11	-	-	-	-	-	-	200	0.74	J49 220 100033	
		125	35	169.5	140x110	105x80/75	11	-	-	-	-	-	-	-	350	1.89	J49 220 125035
		125	40	169.5	140x110	105x80/75	11	-	-	-	-	-	-	-	350	2.13	J49 220 125040
		150	40	193	140x110	105x80/75	11	-	-	-	-	-	-	-	300	2.33	J49 220 150040
		175	45	223.5	140x110	105x80/75	12	-	-	-	-	-	-	-	480	2.35	J49 220 175045
		200	50	250	140x110	105x80/75	11	-	-	-	-	-	-	-	600	3.30	J49 220 200050